

DEWALT®

HIGH PRESSURE WASHERS
IDROPULTRICI ALTA PRESSIONE



TOUGH OUTSIDE, EXPERIENCE INSIDE



DXPW 001 E pag. 04

DXPW 002 E pag. 05

DXPW 003 E pag. 06



DXPW 004 E pag. 07

DXPW 005 E pag. 08

DXPW 006 E pag. 09

DXPW 007 E pag. 10

The new range of High Pressure Washers offers increased efficiency and improved resistance for daily use also in most extreme conditions. By combining experience and innovation the new DeWALT range guarantees our expert users the best performances and satisfactory results especially in most demanding professional applications.

La nuova gamma di Idropulitrici ad alta pressione offre una migliore efficienza ed una maggiore resistenza per garantire un utilizzo quotidiano anche nelle condizioni più estreme. Unendo esperienza e innovazione la nuova gamma DeWALT garantisce agli utilizzatori più esperti le migliori performances e i risultati più soddisfacenti soprattutto nei contesti più esigenti.



DXPW 008 E pag. 11

DXPW 009 E pag. 12

DXPW 0010 E pag. 13



DXPW001E



230V - 50HZ



540L/H



150BAR



60°C



2,3KW

Motor Pump

HRM-A



Soft grip handle
Manico con inserti antiscivolo

Built-in electric cable storage
Vano porta cavo elettrico

Rotative switch ON/OFF
Interruttore rotativo ON/OFF

Wheels ø 200 mm
Ruote ø 200 mm




- 3 Axial stainless steel piston wobble plate pump
- Single phase electric motor with thermal protector
- Self priming function
- Built-in detergent suction
- Molded injection break-resistant plastic carter
- Designed for tough daily operating conditions

- Pompa con tre pistoni assiali in acciaio inossidabile comandati dal piattello oscillante
- Motore elettrico monofase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante
- Carter robusto con plastiche stampate ad iniezione
- Pensata per un utilizzo quotidiano in condizioni estreme

TECHNICAL DATA:

Model / Modello	DXPW001E
AR code	13674
EAN code	8016287136747
Max. Pressure (bar)	150
Max Flow Rate l/h	540
Absorbed power (W - Kw)	2300 - 2,3
Type motor (Phase)	1~
RPM	2800
Voltages (V) - Frequency (Hz)	230 - 50
Max Water Temperature (C°)	60
Weight (kg)	23
Pump material	Aluminum
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW002E



230V - 50HZ



500L/H



150BAR



60°C



2,7KW

Motor Pump

HRM-0



Soft grip handle
Manico con inserti antiscivolo

Built-in electric cable storage
Vano porta cavo elettrico

Rotative switch ON/OFF
Interruttore rotativo ON/OFF

Wheels ø 200 mm
Ruote ø 200 mm



- 3 Axial stainless steel piston wobble plate pump
- Brass pump head
- Single phase electric motor with thermal protector
- Built-in detergent suction
- Self priming function
- Molded injection break-resistant plastic carter
- Designed for tough daily operating conditions
- Pompa con tre pistoni assiali in acciaio inossidabile comandati dal piattello oscillante
- Testa pompa in ottone
- Motore elettrico monofase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante
- Carter robusto con plastiche stampate ad iniezione
- Pensata per un utilizzo quotidiano in condizioni estreme

TECHNICAL DATA:

Model / Modello	DXPW001E
AR code	13675
EAN code	8016287136754
Max. Pressure (bar)	150
Max Flow Rate l/h (High Pressure)	500
Absorbed power (W - Kw)	2700 - 2,7
Type motor (Phase)	1~
RPM	2800
Voltages (V) - Frequency (Hz)	230 - 50
Max Water Temperature (C°)	60
Weight (kg)	27
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW003E



230V - 50HZ



630L/H



130BAR



60°C



2,9KW

Motor Pump

HPV-0



Soft grip handle
Manico con inserti antiscivolo

Built-in electric cable storage
Vano porta cavo elettrico

Rotative switch ON/OFF
Interruttore rotativo ON/OFF

Wheels ø 200 mm
Ruote ø 200 mm



- Triplex pump with ceramic pistons and connecting rod system
- Regulation valve integrated in the pump head
- Brass pump head
- Single phase electric motor with thermal protector
- Built-in detergent suction
- Self priming function
- Molded injection break-resistant plastic carter
- Pensata per un utilizzo quotidiano in condizioni estreme
- Pompa con tre pistoni assiali in ceramica con sistema a biella-manovella
- Valvola di regolazione pressione integrata nella testa della pompa
- Testa pompa in ottone
- Motore elettrico monofase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante
- Carter robusto con plastiche stampate ad iniezione
- Designed for tough daily operating conditions

TECHNICAL DATA:

Model / Modello	DXPW003E
AR code	13676
EAN code	8016287136761
Max. Pressure (bar)	130
Max Flow Rate l/h (High Pressure)	630
Absorbed power (W - Kw)	2900 - 2,9
Type motor (Phase)	1~
RPM	2800
Voltages (V) - Frequency (Hz)	230 - 50
Max Water Temperature (C°)	60
Weight (kg)	27
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW004E



230V - 50HZ



600L/H



150BAR



60°C



3KW

Motor Pump

HRC-0



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori

Foldable aluminium frame
Telaio in alluminio pieghevole

Wheels ø 300 mm
Ruote ø 300 mm

- Heavy-duty two wheeled trolley with handle
- Triplex pump with ceramic pistons and connecting rod system
- Regulation valve integrated in the pump head (minimatic TSS)
- Brass pump head
- Pressure gauge
- Single phase electric motor with thermal protector
- Built-in detergent suction
- Self priming function
- Carrello robusto in metallo a due ruote completo di manico
- Pompa con tre pistoni assiali in ceramica con sistema a biella-manovella
- Valvola di regolazione integrata nella testa della pompa (minimatic TSS)
- Testa pompa in ottone
- Manometro
- Motore elettrico monofase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW004E
AR code	25156
EAN code	8016287251563
Max. Pressure (bar)	150
Max Flow Rate l/h (High Pressure)	600
Absorbed power (W - Kw)	3000 - 3
Type motor (Phase)	1~
RPM	1450
Voltages (V) - Frequency (Hz)	230 - 50
Max Water Temperature (C°)	60
Weight (kg)	38
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW005E



400V - 50HZ



810 L/H



200 BAR



60°C



5 KW

Motor Pump

HRC-0



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori

Foldable aluminium frame
Telaio in alluminio pieghevole

Wheels ø 300 mm
Ruote ø 300 mm

- Heavy-duty two wheeled trolley with handle
- Triplex pump with ceramic pistons and connecting rod system
- regulation valve integrated in the pump head (VRZ TSS)
- Brass pump head
- Pressure gauge
- Three phase electric motor with thermal protector
- Built-in detergent suction
- Self priming function
- Carrello robusto in metallo a due ruote completo di manico
- Pompa con tre pistoni assiali in ceramica con sistema a biella-manovella
- Valvola di regolazione integrata nella testa della pompa (VRZ TSS)
- Testa pompa in ottone
- Manometro
- Motore elettrico trifase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW005E
AR code	25157
EAN code	8016287251570
Max. Pressure (bar)	200
Max Flow Rate l/h (High Pressure)	810
Absorbed power (W - Kw)	5000 - 5
Type motor (Phase)	3~
RPM	1450
Voltages (V) - Frequency (Hz)	400-50
Max Water Temperature (C°)	60
Weight (kg)	40
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW006E



400V - 50HZ



900L/H



170BAR



60°C



5KW

Motor Pump

HRR-0



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori

Foldable aluminium frame
Telaio in alluminio pieghevole

Wheels ø 300 mm
Ruote ø 300 mm

- Heavy-duty two wheeled trolley with handle
- Triplex pump with ceramic pistons and connecting rod system
- regulation valve integrated in the pump head (VRZ TSS)
- Brass pump head
- Pressure gauge
- Three phase electric motor with thermal protector
- Built-in detergent suction
- Self priming function
- Carrello robusto in metallo a due ruote completo di manico
- Pompa con tre pistoni assiali in ceramica con sistema a biella-manovella
- Valvola di regolazione integrata nella testa della pompa (VRZ TSS)
- Testa pompa in ottone
- Manometro
- Motore elettrico trifase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW006E
AR code	25158
EAN code	8016287251587
Max. Pressure (bar)	170
Max Flow Rate l/h (High Pressure)	900
Absorbed power (W - Kw)	5000 - 5
Type motor (Phase)	3~
RPM	1450
Voltages (V) - Frequency (Hz)	400-50
Max Water Temperature (C°)	60
Weight (kg)	40
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW007E



400V - 50HZ



840L/H



230BAR



60°C



7,4KW

Motor Pump

HRR-0



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori

Foldable aluminium frame
Telaio in alluminio pieghevole



Wheels ø 300 mm
Ruote ø 300 mm

- Heavy-duty two wheeled trolley with handle
- Triplex pump with ceramic pistons and connecting rod system
- regulation valve integrated in the pump head (VRZ TSS)
- Brass pump head
- Pressure gauge
- Three phase electric motor with thermal protector
- Built-in detergent suction
- Self priming function
- Carrello robusto in metallo a due ruote completo di manico
- Pompa con tre pistoni assiali in ceramica con sistema a biella-manovella
- Valvola di regolazione integrata nella testa della pompa (VRZ TSS)
- Testa pompa in ottone
- Manometro
- Motore elettrico trifase a induzione con protezione termica
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW007E
AR code	25159
EAN code	8016287251594
Max. Pressure (bar)	230
Max Flow Rate l/h (High Pressure)	840
Absorbed power (W - Kw)	7400 - 7,4
Type motor (Phase)	3~
RPM	1450
Voltages (V) - Frequency (Hz)	400-50
Max Water Temperature (C°)	60
Weight (kg)	64
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW008E



Gasoline engine
Motore a scoppio



600L/H



190BAR



60°C



5,5HP

Motor Pump

POWERED by
HONDA

RC



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori



Wheels ø 280 mm
Ruote ø 280 mm

- Two-wheeled trolley with rubber tread wheels, handle and dumper feet inflatable pneumatic wheels and anti-vibrating feet
- Piston pump with connecting rod system
- Brass pump head
- Regulation valve integrated in the pump head (VRZ)
- Pressure gauge
- Powered by Honda with oil level sensor and inspectable levels
- Built-in detergent suction
- Self priming function

- Carrello completo di manico con due ruote con battistrada in gomma e piedini antivibranti
- Pompa a pistoni con sistema biella-manovella
- Testa pompa in ottone
- Valvola di regolazione integrata nella testa della pompa (VRZ)
- Manometro
- Motorizzato Honda con sensore mancanza olio e livelli ispezionabili
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW008E
AR code	25160
EAN code	8016287251600
Max. Pressure (bar)	190
Max Flow Rate l/h	600
Motor power (HP)	5,5
Type motor	Thermik (GX 160)
RPM	3400
Max Water Temperature (C°)	60
Weight (kg)	30
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW009E



Gasoline engine
Motore a scoppio



780L/H



210BAR



60°C



9HP

Motor Pump

POWERED by
HONDA

RR



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori




Wheels ø 280 mm
Ruote ø 280 mm

- Two-wheeled trolley with rubber tread wheels, handle and dumper feet inflatable pneumatic wheels and anti-vibrating feet
- Piston pump with connecting rod system
- Brass pump head
- Regulation valve integrated in the pump head (VRZ)
- Pressure gauge
- Powered by Honda with oil level sensor and inspectable levels
- Built-in detergent suction
- Self priming function
- Carrello completo di manico con due ruote con battistrada in gomma e piedini antivibranti
- Pompa a pistoni con sistema biella-manovella
- Testa pompa in ottone
- Valvola di regolazione integrata nella testa della pompa (VRZ)
- Manometro
- Motorizzato Honda con sensore mancanza olio e livelli ispezionabili
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW009E
AR code	25161
EAN code	8016287251617
Max. Pressure (bar)	210
Max Flow Rate l/h (High Pressure)	780
Motor power (HP)	9
Type motor	Thermik (GX 270)
RPM	3400
Max Water Temperature (C°)	60
Weight (kg)	42
Pump material	Brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DXPW010E



Gasoline engine
Motore a scoppio



900L/H



270BAR



60°C



13HP

Motor Pump

POWERED by
HONDA

RK



Soft grip handle
Manico con inserti antiscivolo

Built-in accessories holder
Porta accessori



Wheels ø 280 mm
Ruote ø 280 mm

- Two-wheeled trolley with rubber tread wheels, handle and dumper feet inflatable pneumatic wheels and anti-vibrating feet
- Piston pump with connecting rod system
- Brass pump head
- regulation valve integrated in the pump head (VRZ)
- Pressure gauge
- Powered by Honda with oil level sensor and inspectable levels
- Built-in detergent suction
- Self priming function

- Carrello completo di manico con due ruote con battistrada in gomma e piedini antivibranti
- Pompa a pistoni con sistema biella-manovella
- Testa pompa in ottone
- Valvola di regolazione integrata nella testa della pompa (VRZ)
- Manometro
- Motorizzato Honda con sensore mancanza olio e livelli ispezionabili/
- Aspirazione detergente incorporata
- Funzione autoadescante

TECHNICAL DATA:

Model / Modello	DXPW010E
AR code	25162
EAN code	8016287251624
Max. Pressure (bar)	270
Max Flow Rate l/h (High Pressure)	900
Motor power (HP)	13
Type motor	Thermik (GX 390)
RPM	3400
Max Water Temperature (C°)	60
Weight (kg)	50
Pump material	Nichel plated brass
Total Stop System	•
Self priming	•

STANDARD ACCESSORIES:



DEWALT





DEWALT®

DEWALT



Dati, descrizioni ed illustrazioni sono forniti a titolo indicativo e non impegnativo.
Characteristics and descriptions are not binding.



Annovi Reverberi spa
Cleaning Division:
Via Aldo Moro 40,
41030 Bomporto, Mo (Italy)
Tel +39 059 8199 011
Fax + 39 059 8199 000
infoar@annovireverberi.it
www.annovireverberi.it

All rights reserved. Neither this catalogue, nor its text, illustrations, drawings or any part thereof, may be reproduced, stored in a retrieval system, photocopied, recorded or transmitted in any form, whether electronic or otherwise, without Stanley's consent. To the best of Stanley's knowledge, all descriptions, illustrations and prices contained in this catalogue are correct at the time of going to print. Stanley cannot however, be held liable for any inaccuracies of description or illustration and reserve the right to change prices without notification. Orders are subject to minimum box quantities. We reserve the right to amend specifications without prior notice. ©DeWalt Works 2016